



Materiale	PVDF V0 secondo UL94
Guarnizione	FKM
Protezione	IP 68 – 10 bar / IP 69 K con O-ring aggiuntivo
NEMA type rating	4 / 4X / 6
Temperatura di impiego	da -35°C a +150°C
Colore	naturale

RoHS

- // O-Ring montato su richiesta
- // Altri materiali di tenuta su richiesta

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Art.
PG 7	2 – 5	8	21	15/15	1,5	1.299.0700.15
PG 7	3 – 6,5	8	21	15/15	1,5	1.299.0700.14
PG 9	2 – 6	8	22	19/19	2	1.299.0900.15
PG 9	4 – 8	8	22	19/19	2	1.299.0900.14
PG 11	3 – 7	8	25	22/22	3	1.299.1100.15
PG 11	5 – 10	8	25	22/22	3	1.299.1100.14
PG 13,5	5 – 9	9	27	24/24	3	1.299.1300.15
PG 13,5	6 – 12	9	27	24/24	3	1.299.1300.14
PG 16	7 – 12	10	28	27/27	3,5	1.299.1600.15
PG 16	10 – 14	10	28	27/27	4,5	1.299.1600.14
PG 21	9 – 16	11	31	33/33	4	1.299.2100.15
PG 21	13 – 18	11	31	33/33	4	1.299.2100.14
PG 29	13 – 20	11	39	42/42	6	1.299.2900.15
PG 29	18 – 25	11	39	42/42	6	1.299.2900.14
PG 36	20 – 26	13	48	53/53	9	1.299.3600.15
PG 36	22 – 32	13	48	53/53	10	1.299.3600.14
PG 42	25 – 31	13	49	60/60	11	1.299.4200.15
PG 42	32 – 38	13	49	60/60	15	1.299.4200.14
PG 48	29 – 35	14	49	65/65	10	1.299.4800.15
PG 48	37 – 44	14	49	65/65	18	1.299.4800.14

