


Pressacavi in plastica

HSK-W (metrico, PG, NPT)



Materiale	Poliammide
Guarnizione	NBR
Materiale o-ring	NBR
Protezione	IP 68
Temperatura di impiego	da -40°C a +100°C
Colore	nero / grigio
RAL	9005 / 7035

RoHS

// Altre guarnizioni es. guarnizioni in silicone su richiesta

AG	∅k mm	GL mm	H mm	L mm	SW mm	Nm	Art. grigio	Art. nero
M16 x 1,5	2 - 6	8	23	45	19	2,5	1.313.1600.51	1.313.1601.51
M16 x 1,5	4 - 8	8	23	45	19	2,5	1.313.1600.50	1.313.1601.50
M20 x 1,5	5 - 9	9	30,5	57	24	4	1.313.2000.51	1.313.2001.51
M20 x 1,5	6 - 12	9	30,5	57	24	4	1.313.2000.50	1.313.2001.50
M25 x 1,5	9 - 16	11	40	73	33	6	1.313.2500.51	1.313.2501.51
M25 x 1,5	13 - 18	11	40	73	33	6	1.313.2500.50	1.313.2501.50
M32 x 1,5	13 - 20	11	51,5	91	42	9	1.313.3200.51	1.313.3201.51
M32 x 1,5	18 - 25	11	51,5	91	42	9	1.313.3200.50	1.313.3201.50
PG 9	2 - 6	8	23	45	19	2,5	1.313.0900.15	1.313.0901.15
PG 9	4 - 8	8	23	45	19	2,5	1.313.0900.14	1.313.0901.14
PG 11	3 - 7	8	27	50	22	2,5	1.313.1100.15	1.313.1101.15
PG 11	5 - 10	8	27	50	22	4	1.313.1100.14	1.313.1101.14
PG 13,5	5 - 9	9	30,5	57	24	4	1.313.1300.15	1.313.1301.15
PG 13,5	6 - 12	9	30,5	57	24	4	1.313.1300.14	1.313.1301.14
PG 16	7 - 12	10	32,5	59	27	4	1.313.1600.15	1.313.1601.15
PG 16	10 - 14	10	32,5	59	27	6	1.313.1600.14	1.313.1601.14
PG 21	9 - 16	11	40	73	33	6	1.313.2100.15	1.313.2101.15
PG 21	13 - 18	11	40	73	33	6	1.313.2100.14	1.313.2101.14
PG 29	13 - 20	11	51,5	91	42	9	1.313.2900.15	1.313.2901.15
PG 29	18 - 25	11	51,5	91	42	9	1.313.2900.14	1.313.2901.14
NPT 3/8"	2 - 6	15	23	45	19	2,5	1.313.3800.71	1.313.3801.71
NPT 3/8"	4 - 8	15	23	45	19	2,5	1.313.3800.70	1.313.3801.70
NPT 1/2"	5 - 9	13	32,5	57	24	4	1.313.1200.71	1.313.1201.71
NPT 1/2"	6 - 12	13	32,5	57	24	4	1.313.1200.70	1.313.1201.70
NPT 1/2"	7 - 12	13	32,5	59	27	4	1.313.1216.71	1.313.1217.71
NPT 1/2"	10 - 14	13	32,5	59	27	6	1.313.1216.70	1.313.1217.70
NPT 3/4"	9 - 16	13	40	73	33	6	1.313.3400.71	1.313.3401.71
NPT 3/4"	13 - 18	13	40	73	33	6	1.313.3400.70	1.313.3401.70
NPT 1"	13 - 20	19	51,5	91	42	9	1.313.1000.71	1.313.1001.71
NPT 1"	18 - 25	19	51,5	91	42	9	1.313.1000.70	1.313.1001.70

