


# Pressacavi in plastica

HSK-W-Flex (metrico, PG, NPT)



|                        |                   |
|------------------------|-------------------|
| Materiale              | Poliammide        |
| Guarnizione            | NBR               |
| Materiale o-ring       | NBR               |
| Protezione             | IP 68             |
| Temperatura di impiego | da -40°C a +100°C |
| Colore                 | grigio / nero     |
| RAL                    | 7035 / 9005       |

RoHS

// Altre guarnizioni es. guarnizioni in silicone su richiesta

| AG        | Øk<br>mm | d<br>mm | GL<br>mm | H<br>mm | L<br>mm | SW<br>mm | ⌀<br>Nm | Art.<br>grigio | Art.<br>nero  |
|-----------|----------|---------|----------|---------|---------|----------|---------|----------------|---------------|
| M16 x 1,5 | 2-6      | 8,5     | 8        | 23      | 85      | 19       | 2,5     | 1.314.1600.51  | 1.314.1601.51 |
| M16 x 1,5 | 4-8      | 8,5     | 8        | 23      | 85      | 19       | 2,5     | 1.314.1600.50  | 1.314.1601.50 |
| M20 x 1,5 | 5-9      | 13      | 9        | 30,5    | 119     | 24       | 4       | 1.314.2000.51  | 1.314.2001.51 |
| M20 x 1,5 | 6-12     | 13      | 9        | 30,5    | 119     | 24       | 4       | 1.314.2000.50  | 1.314.2001.50 |
| M25 x 1,5 | 9-16     | 20      | 11       | 40      | 156     | 33       | 6       | 1.314.2500.51  | 1.314.2501.51 |
| M25 x 1,5 | 13-18    | 20      | 11       | 40      | 156     | 33       | 6       | 1.314.2500.50  | 1.314.2501.50 |
| PG 9      | 2-6      | 8,5     | 8        | 23      | 85      | 19       | 2,5     | 1.314.0900.15  | 1.314.0901.15 |
| PG 9      | 4-8      | 8,5     | 8        | 23      | 85      | 19       | 2,5     | 1.314.0900.14  | 1.314.0901.14 |
| PG 11     | 3-7      | 10,5    | 8        | 27      | 103     | 22       | 2,5     | 1.314.1100.15  | 1.314.1101.15 |
| PG 11     | 5-10     | 10,5    | 8        | 27      | 103     | 22       | 4       | 1.314.1100.14  | 1.314.1101.14 |
| PG 13,5   | 5-9      | 13      | 9        | 30,5    | 119     | 24       | 4       | 1.314.1300.15  | 1.314.1301.15 |
| PG 13,5   | 6-12     | 13      | 9        | 30,5    | 119     | 24       | 4       | 1.314.1300.14  | 1.314.1301.14 |
| PG 16     | 7-12     | 15,5    | 10       | 32,5    | 130     | 27       | 4       | 1.314.1600.15  | 1.314.1601.15 |
| PG 16     | 10-14    | 15,5    | 10       | 32,5    | 130     | 27       | 6       | 1.314.1600.14  | 1.314.1601.14 |
| PG 21     | 9-16     | 20      | 11       | 40      | 156     | 33       | 6       | 1.314.2100.15  | 1.314.2101.15 |
| PG 21     | 13-18    | 20      | 11       | 40      | 156     | 33       | 6       | 1.314.2100.14  | 1.314.2101.14 |
| NPT 3/8"  | 2-6      | 8,5     | 15       | 23      | 85      | 19       | 2,5     | 1.314.3800.71  | 1.314.3801.71 |
| NPT 3/8"  | 4-8      | 8,5     | 15       | 23      | 85      | 19       | 2,5     | 1.314.3800.70  | 1.314.3801.70 |
| NPT 1/2"  | 5-9      | 13      | 13       | 30,5    | 119     | 24       | 4       | 1.314.1200.71  | 1.314.1201.71 |
| NPT 1/2"  | 6-12     | 13      | 13       | 30,5    | 119     | 24       | 4       | 1.314.1200.70  | 1.314.1201.70 |
| NPT 1/2"  | 7-12     | 15,5    | 13       | 31,5    | 130     | 27       | 4       | 1.314.1216.71  | 1.314.1217.71 |
| NPT 1/2"  | 10-14    | 15,5    | 13       | 31,5    | 130     | 27       | 6       | 1.314.1216.70  | 1.314.1217.70 |
| NPT 3/4"  | 9-16     | 20      | 13       | 40      | 156     | 33       | 6       | 1.314.3400.71  | 1.314.3401.71 |
| NPT 3/4"  | 13-18    | 20      | 13       | 40      | 156     | 33       | 6       | 1.314.3400.70  | 1.314.3401.70 |

