



Materiale	Poliammide V0 secondo UL94
Guarnizione	NBR
Protezione	IP 68 – 10 bar / IP 69 K con O-ring aggiuntivo
NEMA type rating	4 / 4X / 6
Temperatura di impiego	da -40°C a +100°C
Colore	grigio / nero
RAL	7035 / 9005

RoHS

- // O-Ring montato su richiesta
- // Altri materiali di tenuta su richiesta

AG	∅k mm	d mm	GL mm	H mm	SW1/SW2 mm	⊕ Nm	Art. grigio	Art. nero
PG 7	2 – 6	7	8	22	19/19	2	1.590.0700.15	1.590.0701.15
PG 7	4 – 8	7	8	22	19/19	2	1.590.0700.14	1.590.0701.14
PG 9	3 – 7	9	8	25	22/22	2,5	1.590.0900.15	1.590.0901.15
PG 9	5 – 10	9	8	25	22/22	3	1.590.0900.14	1.590.0901.14
PG 11	5 – 9	10,5	8	24	24/24	3	1.590.1100.15	1.590.1101.15
PG 11	6 – 12	10,5	8	24	24/24	4,5	1.590.1100.14	1.590.1101.14
PG 13,5	7 – 12	12,5	9	28	27/27	3,5	1.590.1300.15	1.590.1301.15
PG 13,5	10 – 14	12,5	9	28	27/27	4,5	1.590.1300.14	1.590.1301.14
PG 16	9 – 16	15	10	31	33/33	4	1.590.1600.15	1.590.1601.15
PG 16	13 – 18	15	10	31	33/33	5	1.590.1600.14	1.590.1601.14

