



Materiale	Poliammide VO secondo UL94
Guarnizione	NBR
Protezione	IP 68 – 10 bar / IP 69 K con O-ring aggiuntivo
NEMA type rating	4 / 4X / 6
Temperatura di impiego	da -40°C a +100°C
Colore	grigio / nero
RAL	7035 / 9005

RoHS

// O-Ring montato su richiesta

// Altri materiali di tenuta su richiesta



AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Art. grigio	Art. nero
PG 9	2 – 5	8	21	15/19	1,5	1.591.0900.15	1.591.0901.15
PG 9	3 – 6,5	8	21	15/19	1,5	1.591.0900.14	1.591.0901.14
PG 11	2 – 6	8	22	19/22	2	1.591.1100.15	1.591.1101.15
PG 11	4 – 8	8	22	19/22	2	1.591.1100.14	1.591.1101.14
PG 13,5	3 – 7	9	25	22/24	2,5	1.591.1300.15	1.591.1301.15
PG 13,5	5 – 10	9	25	22/24	3	1.591.1300.14	1.591.1301.14
PG 16	5 – 9	10	27	24/27	3	1.591.1600.15	1.591.1601.15
PG 16	6 – 12	10	27	24/27	4,5	1.591.1600.14	1.591.1601.14
PG 21	7 – 12	11	28	27/33	3,5	1.591.2100.15	1.591.2101.15
PG 21	10 – 14	11	28	27/33	4,5	1.591.2100.14	1.591.2101.14

