


Flangia a 90° FW-ZN (metrico, PG)



Materiale	Zinco pressofuso
Materiale o-ring	NBR
Protezione	IP 65
Temperatura di impiego	da -20°C a +95°C

RoHS

IG	Ø mm	H mm	C mm	D mm	E mm	Art.
M20 x 1,5	5,5	35	56	53	44	1.306.2000.50
M25 x 1,5	5,5	42	65	63	54	1.306.2500.50
M32 x 1,5	5,5	52	75	71	60	1.306.3200.50
M50 x 1,5	6,5	69	93	89	72	1.306.5000.50
M63 x 1,5	6,5	74	114	96	84	1.306.6300.50
PG 9	4,3	30	50	45	37	1.306.0900.05
PG 11	4,3	30	50	45	37	1.306.1100.05
PG 13,5	5,5	35	56	53	44	1.306.1300.05
PG 16	5,5	35	56	53	44	1.306.1600.05
PG 21	5,5	42	65	63	54	1.306.2100.05
PG 29	5,5	52	74	70	60	1.306.2900.05
PG 36	6,5	69	94	89	72	1.306.3600.05
PG 42	6,5	74	114	96	84	1.306.4200.05
PG 48	6,5	74	114	96	84	1.306.4800.05