


Guarnizione in materiale composito di fibra



Materiale

Fibra composita

RoHS

Temperatura di impiego

da -50°C a +250°C

Adatto per AG	d mm	D mm	s mm	Art.
M12 x 1,5	12	16	2	1.325.1200.50
M16 x 1,5	16	20	2	1.325.1600.50
M20 x 1,5	20	25	2	1.325.2000.50
M25 x 1,5	25	31	2	1.325.2500.50
M32 x 1,5	32	38	2	1.325.3200.50
M40 x 1,5	40	48	2	1.325.4000.50
M50 x 1,5	50	58	2	1.325.5000.50
M63 x 1,5	63	72	2	1.325.6300.50
PG 7	12,5	16,5	1,5	1.325.0700.20
PG 9	15,2	19	1,5	1.325.0900.20
PG 11	18,6	22,5	1,5	1.325.1100.20
PG 13,5	20,4	25	1,5	1.325.1300.20
PG 16	22,5	27	1,5	1.325.1600.20
PG 21	28,3	33,5	2	1.325.2100.20
PG 29	37	43,5	2	1.325.2900.20
PG 36	47	55	2	1.325.3600.20
PG 42	54	63	2	1.325.4200.20
PG 48	59,3	69	2	1.325.4800.20