



Materiale	Ottone nichelato
Inserto di serraggio	Poliammide VO secondo UL94
Guarnizione	NBR
Materiale o-ring	NBR
Protezione	IP 68 – 10 bar / IP 69 K
Livello protezione ATEX	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
NEMA type rating	4 / 4X / 6
Temperatura di impiego	da -20°C a +95°C / da -60°C a +95°C

RoHS

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Art. da -20°C a +95°C	Art. da -60°C a +95°C
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.610.1200.51	1.640.1200.51
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.610.1200.50	1.640.1200.50
M16 x 1,5	2 – 6	6	21	17/19	6	1.610.1600.51	1.640.1600.51
M16 x 1,5	3 – 7	6	22	20/20	5	1.610.1611.51	1.640.1611.51
M16 x 1,5	4 – 8	6	21	17/19	6	1.610.1600.50	1.640.1600.50
M16 x 1,5	5 – 10	6	22	20/20	5	1.610.1611.50	1.640.1611.50
M20 x 1,5	5 – 9	6	23	22/22	8	1.610.2000.51	1.640.2000.51
M20 x 1,5	6 – 12	6	23	22/22	8	1.610.2000.50	1.640.2000.50
M20 x 1,5	7 – 12	6	24	24/24	10	1.610.2016.51	1.640.2016.51
M20 x 1,5	10 – 14	6	24	24/24	10	1.610.2016.50	1.640.2016.50
M25 x 1,5	10 – 16	7	26	30/30	12	1.610.2500.51	1.640.2500.51
M25 x 1,5	14 – 18	7	26	30/30	12	1.610.2500.50	1.640.2500.50
M32 x 1,5	13 – 20	8	31	40/40	15	1.610.3200.51	1.640.3200.51
M32 x 1,5	20 – 25	8	31	40/40	15	1.610.3200.50	1.640.3200.50
M40 x 1,5	20 – 26	8	37	50/50	15	1.610.4000.51	1.640.4000.51
M40 x 1,5	22 – 32	8	37	50/50	15	1.610.4000.50	1.640.4000.50
M50 x 1,5	25 – 31	9	37	57/57	24	1.610.5000.51	1.640.5000.51
M50 x 1,5	32 – 38	9	37	57/57	24	1.610.5000.50	1.640.5000.50
M63 x 1,5	29 – 35	10	38	64/68	30	1.610.6300.51	1.640.6300.51
M63 x 1,5	37 – 44	10	38	64/68	30	1.610.6300.50	1.640.6300.50



alle istruzioni di
montaggio



ATEX^{Ex}