



Materiale	Ottone nichelato
Inserto di serraggio	Poliammide VO secondo UL94
Guarnizione	NBR
Materiale o-ring	NBR
Protezione	IP 68 – 10 bar / IP 69 K
Livello protezione ATEX	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
NEMA type rating	4 / 4X / 6
Temperatura di impiego	da -20°C a +95°C / da -60°C a +95°C

RoHS

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Art. da -20°C a +95°C	Art. da -60°C a +95°C
PG 7	2 – 5	5	19	14/14	4	1.610.0700.15	1.640.0700.15
PG 7	3 – 6,5	5	19	14/14	4	1.610.0700.01	1.640.0700.01
PG 9	2 – 6	6	21	17/17	6	1.610.0900.15	1.640.0900.15
PG 9	4 – 8	6	21	17/17	6	1.610.0900.01	1.640.0900.01
PG 11	3 – 7	6	22	20/20	5	1.610.1100.15	1.640.1100.15
PG 11	5 – 10	6	22	20/20	5	1.610.1100.01	1.640.1100.01
PG 13,5	5 – 9	6,5	24	22/22	8	1.610.1300.15	1.640.1300.15
PG 13,5	6 – 12	6,5	24	22/22	8	1.610.1300.01	1.640.1300.01
PG 16	7 – 12	6,5	23	24/24	10	1.610.1600.15	1.640.1600.15
PG 16	10 – 14	6,5	23	24/24	10	1.610.1600.01	1.640.1600.01
PG 21	10 – 16	7	24	30/30	12	1.610.2100.15	1.640.2100.15
PG 21	14 – 18	7	24	30/30	12	1.610.2100.01	1.640.2100.01
PG 29	13 – 20	8	29	40/40	15	1.610.2900.15	1.640.2900.15
PG 29	20 – 25	8	29	40/40	15	1.610.2900.01	1.640.2900.01
PG 36	20 – 26	8	35	50/50	15	1.610.3600.15	1.640.3600.15
PG 36	22 – 32	8	35	50/50	15	1.610.3600.01	1.640.3600.01
PG 42	25 – 31	9	37	57/57	24	1.610.4200.15	1.640.4200.15
PG 42	32 – 38	9	37	57/57	24	1.610.4200.01	1.640.4200.01
PG 48	29 – 35	10	38	64/64	30	1.610.4800.15	1.640.4800.15
PG 48	37 – 44	10	38	64/64	30	1.610.4800.01	1.640.4800.01



alle istruzioni di
montaggio



ATEX^{Ex}