



Materiale	Ottone nichelato
Inserto di serraggio	Poliammide VO secondo UL94
Guarnizione	NBR
Materiale o-ring	NBR
Protezione	IP 68 – 10 bar / IP 69 K
Livello protezione ATEX	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
NEMA type rating	4 / 4X / 6
Temperatura di impiego	da -20°C a +95°C / da -60°C a +95°C

RoHS

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⚙ Nm	Art. da -20°C a +95°C	Art. da -60°C a +95°C
NPT 3/8"	2 – 6	15	21	17/19	6	1.610.3800.71	1.640.3800.71
NPT 3/8"	4 – 8	15	21	17/19	6	1.610.3800.70	1.640.3800.70
NPT 1/2"	5 – 9	13	24	22/24	8	1.610.1200.71	1.640.1200.71
NPT 1/2"	6 – 12	13	24	22/24	8	1.610.1200.70	1.640.1200.70
NPT 3/4"	10 – 16	13	25	30/30	12	1.610.3400.71	1.640.3400.71
NPT 3/4"	14 – 18	13	25	30/30	12	1.610.3400.70	1.640.3400.70
NPT 1"	13 – 20	19	29	40/40	15	1.610.1000.71	1.640.1000.71
NPT 1"	20 – 25	19	29	40/40	15	1.610.1000.70	1.640.1000.70



alle istruzioni di
montaggio



ATEX^{Ex}