



Materiale	Ottone nichelato
Inserto di serraggio	Poliammide V0 secondo UL94
Guarnizione	FKM
Protezione	IP 68 – 10 bar / IP 69 K
Livello protezione ATEX	II 1D Ex ta IIIC Da / II 2G Ex db IIC Gb
Temperatura di impiego	da -60°C a +105°C

RoHS

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	Nm	Art.
NPT 3/8"	3 – 7	16	22	20/20	9	1.622.3800.71
NPT 3/8"	5 – 10	16	22	20/20	9	1.622.3800.70
NPT 1/2"	7 – 12	20	25	24/24	10	1.622.1200.71
NPT 1/2"	10 – 14	20	25	24/24	10	1.622.1200.70
NPT 3/4"	9 – 16	20,5	26,5	30/30	12	1.622.3400.71
NPT 3/4"	13 – 18	20,5	26,5	30/30	12	1.622.3400.70
NPT 1"	14 – 20	25	32	40/40	15	1.622.1000.71
NPT 1"	18 – 25	25	32	40/40	15	1.622.1000.70
NPT 1 1/4"	20 – 26	26	38,5	50/50	24	1.622.5400.71
NPT 1 1/4"	22 – 32	26	38,5	50/50	24	1.622.5400.70
NPT 1 1/2"	20 – 26	26,5	38,5	50/50	24	1.622.6400.71
NPT 1 1/2"	22 – 32	26,5	38,5	50/50	24	1.622.6400.70



alle istruzioni di
montaggio

