



Materiale	Ottone nichelato
Inserto di serraggio	Poliammide
Guarnizione	NBR
Materiale o-ring	NBR
Protezione	IP 68 – 5 bar
Temperatura di impiego	da -40°C a +100°C

RoHS

EMV
EMC

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	Nm	Art.
M12 x 1,5	3 – 6,5	6	19,4	14/14	3	1.607.1200.50
M16 x 1,5	4,5 – 10	6	24,4	19/19	6,5	1.607.1600.50
M20 x 1,5	6 – 12	6	25,4	22/22	6	1.607.2013.50
M20 x 1,5	7,5 – 14	6	28,3	24/24	8	1.607.2000.50
M25 x 1,5	9 – 17	7	29,3	29/29	9,5	1.607.2500.50
M32 x 1,5	11 – 21	8	37,7	34/34	13,5	1.607.3200.50
M40 x 1,5	19 – 28	8	40,7	44/44	32	1.607.4000.50
M50 x 1,5	27 – 35	9	50,7	55/55	40	1.607.5000.50
M63 x 1,5	34 – 48	10	55,7	68/68	46	1.607.6300.50



al video del prodotto



alle istruzioni di
montaggio

