



Materiale	INOX 1.4305
Inserto di serraggio	Poliammide VO secondo UL94
Guarnizione	NBR
Materiale o-ring	NBR
Protezione	IP 68 – 10 bar / IP 69 K
NEMA type rating	4 / 4X / 6
Temperatura di impiego	da -40°C a +100°C

RoHS

EMV
EMC

// Altri tipi di acciaio disponibili su richiesta

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	Nm	Art.
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.693.1200.51
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.693.1200.50
M16 x 1,5	3 – 7	6	21	22/22	5	1.693.1600.51
M16 x 1,5	5 – 10	6	21	22/22	5	1.693.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.693.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.693.2000.50
M25 x 1,5	9 – 16	7	26	30/30	12	1.693.2500.51
M25 x 1,5	13 – 18	7	26	30/30	12	1.693.2500.50
M32 x 1,5	13 – 20	8	31	41/41	15	1.693.3200.51
M32 x 1,5	18 – 25	8	31	41/41	15	1.693.3200.50
M40 x 1,5	20 – 26	8	37	50/50	15	1.693.4000.51
M40 x 1,5	22 – 32	8	37	50/50	15	1.693.4000.50
PG 7	2 – 5	5	19	14/14	4	1.693.0700.15
PG 7	3 – 6,5	5	19	14/14	4	1.693.0700.01
PG 9	2 – 6	6	21	17/17	6	1.693.0900.15
PG 9	4 – 8	6	21	17/17	6	1.693.0900.01
PG 11	3 – 7	6	22	22/22	5	1.693.1100.15
PG 11	5 – 10	6	22	22/22	5	1.693.1100.01
PG 13,5	5 – 9	6,5	24	22/22	8	1.693.1300.15
PG 13,5	6 – 12	6,5	24	22/22	8	1.693.1300.01
PG 16	7 – 12	6,5	23	24/24	10	1.693.1600.15
PG 16	10 – 14	6,5	23	24/24	10	1.693.1600.01
PG 21	9 – 16	7	24	30/30	12	1.693.2100.15
PG 21	13 – 18	7	24	30/30	12	1.693.2100.01
PG 29	13 – 20	8	29	41/41	15	1.693.2900.15
PG 29	18 – 25	8	29	41/41	15	1.693.2900.01
PG 36	20 – 26	8	35	50/50	15	1.693.3600.15
PG 36	22 – 32	8	35	50/50	15	1.693.3600.01



al video del prodotto

