


Pressacavi DIN

DIN 46320 Plastica (PG)



Materiale	Poliammide
Guarnizione	NBR
Protezione	IP 54 / IP 65 con guarnizione piatta aggiuntiva sulla filettatura di collegamento
Temperatura di impiego	da -20°C a +80°C
Colore	grigio
RAL	7035

RoHS

// Filettatura metrica disponibile su richiesta

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	Art.
PG 7	3,5 – 6	8	20	13/15	1.202.0700.11
PG 9	4 – 10	8	21	16/19	1.202.0901.11
PG 9	4,5 – 7	8	21	16/19	1.202.0900.11
PG 11	6 – 9	8	22	19/22	1.202.1100.11
PG 11	6,5 – 12	8	22	19/22	1.202.1101.11
PG 13,5	6,5 – 13,5	9	26	21/24	1.202.1301.11
PG 13,5	9 – 12	9	26	21/24	1.202.1300.11
PG 16	6,5 – 16	10	28	23/27	1.202.1601.11
PG 16	11 – 14	10	28	23/27	1.202.1600.11
PG 21	9 – 20	11	32	30/33	1.202.2101.11
PG 21	14 – 18	11	32	30/33	1.202.2100.11
PG 29	17 – 28	11	35	40/42	1.202.2901.11
PG 29	18 – 25	11	35	40/42	1.202.2900.11
PG 36	23 – 34	13	39	50/53	1.202.3601.11
PG 36	25 – 32	13	39	50/53	1.202.3600.11
PG 42	29 – 40	13	44	55/60	1.202.4201.11
PG 42	30 – 38	13	44	55/60	1.202.4200.11
PG 48	34 – 42	14	44	60/65	1.202.4800.11
PG 48	35 – 46	14	44	60/65	1.202.4801.11

