


Ghiera di fissaggio GM-FS (metrico, PG, NPT)



Materiale	Poliammide, fibra di vetro rinforzata
Temperatura di impiego	da -40°C a +100°C
Colore	grigio / nero
RAL	7035 / 9005

RoHS

IG	H mm	SW mm	Art. grigio	Art. nero
M12 x 1,5	5	17	1.262.1200.50	1.262.1201.50
M16 x 1,5	5	22	1.262.1600.50	1.262.1601.50
M20 x 1,5	6	27	1.262.2000.50	1.262.2001.50
M25 x 1,5	6,5	32	1.262.2500.50	1.262.2501.50
M32 x 1,5	7	41	1.262.3200.50	1.262.3201.50
M40 x 1,5	7	50	1.262.4000.50	1.262.4001.50
M50 x 1,5	8	60	1.262.5000.50	1.262.5001.50
M63 x 1,5	8	75	1.262.6300.50	1.262.6301.50
PG 7	5	19	1.262.0700.11	1.262.0701.11
PG 9	5	22	1.262.0900.11	1.262.0901.11
PG 11	5	24	1.262.1100.11	1.262.1101.11
PG 13,5	6	27	1.262.1300.11	1.262.1301.11
PG 16	6	30	1.262.1600.11	1.262.1601.11
PG 21	7	36	1.262.2100.11	1.262.2101.11
PG 29	7	46	1.262.2900.11	1.262.2901.11
PG 36	8	60	1.262.3600.11	1.262.3601.11
PG 42	8	65	1.262.4200.11	1.262.4201.11
PG 48	8	70	1.262.4800.11	1.262.4801.11
NPT 3/8"	7	24	1.262.3800.70	1.262.3801.70
NPT 1/2"	7	27	1.262.1200.70	1.262.1201.70
NPT 3/4"	7	32	1.262.3400.70	1.262.3401.70
NPT 1"	8	40	1.262.1000.70	1.262.1001.70