


Tappo V-N-FS (metrico, PG)



Materiale	Poliammide
Protezione	IP 54
Temperatura di impiego	da -40°C a +100°C
Colore	grigio / nero
RAL	7035 / 9005

RoHS



AG	D mm	GL mm	H mm	Art. grigio	Art. nero
M12 x 1,5	15	6	10	1.251.1200.50	1.251.1201.50
M16 x 1,5	20	7	11	1.251.1600.50	
M16 x 1,5	20	7	11,5		1.251.1601.50
M20 x 1,5	25	6	9,5	1.251.2000.50	1.251.2001.50
M25 x 1,5	30	11	15,5	1.251.2500.50	1.251.2501.50
M32 x 1,5	38	11	16	1.251.3200.50	1.251.3201.50
M40 x 1,5	46	13	18	1.251.4000.50	1.251.4001.50
M50 x 1,5	56	13	18,5	1.251.5000.50	1.251.5001.50
M63 x 1,5	69	15	19	1.251.6300.50	1.251.6301.50
PG 7	15	6	8	1.251.0700.11	1.251.0701.11
PG 9	19	6	9	1.251.0900.11	1.251.0901.11
PG 11	22	6	9	1.251.1100.11	1.251.1101.11
PG 13,5	25	6	9,5	1.251.1300.11	1.251.1301.11
PG 16	27	6	9,5	1.251.1600.11	1.251.1601.11
PG 21	33	8	11	1.251.2100.11	1.251.2101.11
PG 29	44	8	12	1.251.2900.11	1.251.2901.11
PG 36	55	10	15	1.251.3600.11	1.251.3601.11
PG 42	62	10	16	1.251.4200.11	1.251.4201.11
PG 48	69	12	16	1.251.4800.11	1.251.4801.11