


Tappo V-NE-Ms-SD (metrico, PG)



Materiale	Ottone nichelato
Materiale o-ring	NBR / FKM
Protezione	IP 68 – 10 bar / IP 69 K
Temperatura di impiego	da -20°C a +95°C / da -20°C a +180°C

RoHS

- // Filettatura NPT su richiesta
- // Filetto lungo su richiesta
- // Altre guarnizioni su richiesta

AG	GL mm	H mm	SW mm	Art. NBR	Art. FKM
M12 x 1,5	6,5	9,5	14	1.156.1200.50	1.157.1200.50
M16 x 1,5	6	9	19	1.156.1600.50	1.157.1600.50
M20 x 1,5	6	9,5	22	1.156.2000.50	1.157.2000.50
M25 x 1,5	7	10,5	30	1.156.2500.50	1.157.2500.50
M32 x 1,5	8	12,5	41	1.156.3200.50	1.157.3200.50
M40 x 1,5	8	13	46	1.156.4000.50	1.157.4000.50
M50 x 1,5	9	15	55	1.156.5000.50	1.157.5000.50
M63 x 1,5	10	16,5	70	1.156.6300.50	1.157.6300.50
PG 7	5	8	14	1.156.0700.01	1.157.0700.01
PG 9	6	9	17	1.156.0900.01	1.157.0900.01
PG 11	6	9,5	20	1.156.1100.01	1.157.1100.01
PG 13,5	6,5	10	22	1.156.1300.01	1.157.1300.01
PG 16	6,5	10	24	1.156.1600.01	1.157.1600.01
PG 21	7	10,5	30	1.156.2100.01	1.157.2100.01
PG 29	8	12,5	41	1.156.2900.01	1.157.2900.01
PG 36	8	13	50	1.156.3600.01	1.157.3600.01
PG 42	9	15	58	1.156.4200.01	1.157.4200.01
PG 48	10	16,5	65	1.156.4800.01	1.157.4800.01