



Materiale	Ottone nichelato
Materiale o-ring	NBR
Protezione	IP 68 – 10 bar / IP 69 K
Livello protezione ATEX	II 2G Ex db eb IIC Gb / II 1D Ex ta IIIC Da
Temperatura di impiego	da -20°C a +95°C

RoHS

AG	IG	GL mm	H mm	SW mm	Art.
M16 x 1,5	M12 x 1,5	16	19	19	1.878.1612.50
M20 x 1,5	M12 x 1,5	16	19,5	22	1.878.2012.50
M20 x 1,5	M16 x 1,5	16	19,5	22	1.878.2016.50
M25 x 1,5	M16 x 1,5	16	19,5	30	1.878.2516.50
M25 x 1,5	M20 x 1,5	16	19,5	30	1.878.2520.50
M32 x 1,5	M16 x 1,5	16	20,5	41	1.878.3216.50
M32 x 1,5	M20 x 1,5	16	20,5	41	1.878.3220.50
M32 x 1,5	M25 x 1,5	16	20,5	41	1.878.3225.50
M40 x 1,5	M20 x 1,5	16	21	46	1.878.4020.50
M40 x 1,5	M25 x 1,5	16	21	46	1.878.4025.50
M40 x 1,5	M32 x 1,5	16	21	46	1.878.4032.50
M50 x 1,5	M25 x 1,5	16	21	55	1.878.5025.50
M50 x 1,5	M32 x 1,5	16	21	55	1.878.5032.50



alle istruzioni di
montaggio

