


Adattatore RSD-MS-VMQ-Ex d (metrico)



Materiale	Ottone nichelato
Materiale o-ring	VMQ (Silicone)
Protezione	IP 68 – 10 bar / IP 69 K
Livello protezione ATEX	II 2G Ex db eb IIC Gb / II 1D Ex ta IIIC Da
Temperatura di impiego	da -60°C a +180°C

RoHS

AG	IG	GL mm	H mm	SW mm	Art.
M16 x 1,5	M12 x 1,5	16	19	19	1.879.1612.50
M20 x 1,5	M12 x 1,5	16	19,5	22	1.879.2012.50
M20 x 1,5	M16 x 1,5	16	19,5	22	1.879.2016.50
M25 x 1,5	M16 x 1,5	16	19,5	30	1.879.2516.50
M25 x 1,5	M20 x 1,5	16	19,5	30	1.879.2520.50
M32 x 1,5	M16 x 1,5	16	20,5	41	1.879.3216.50
M32 x 1,5	M20 x 1,5	16	20,5	41	1.879.3220.50
M32 x 1,5	M25 x 1,5	16	20,5	41	1.879.3225.50
M40 x 1,5	M20 x 1,5	16	21	46	1.879.4020.50
M40 x 1,5	M25 x 1,5	16	21	46	1.879.4025.50
M40 x 1,5	M32 x 1,5	16	21	46	1.879.4032.50
M50 x 1,5	M25 x 1,5	16	21	55	1.879.5025.50
M50 x 1,5	M32 x 1,5	16	21	55	1.879.5032.50



alle istruzioni di
montaggio

